



Bearing No.	Dimensions <small>mm in.</small>			Dynamic load ratings N	Static load ratings N	Weight (kg)
	d	D	B			
SC200	10 0.3937	30 1.1811	9 0.3543	5100	2230	0.031
SC201	12 0.4724	32 1.2598	10 0.3937	6800	3050	0.033
SC202	15 0.5906	35 1.3780	11 0.4331	7600	3490	0.043
SC203	17 0.6693	40 1.5748	12 0.4724	9600	4600	0.061
SC204	20 0.7874	47 1.8504	14 0.5512	12800	6650	0.098
SC205	25 0.9843	52 2.0472	15 0.5906	14000	7850	0.122
SC206	30 1.1811	62 2.4409	16 0.6299	19500	11300	0.195
SC207	35 1.3780	72 2.8346	17 0.6693	25700	15300	0.280
SC208	40 1.5748	80 3.1496	18 0.7087	29500	18100	0.358
SC209	45 1.7717	85 3.3465	19 0.7480	31600	20600	0.405
SC210	50 1.9685	90 3.5433	20 0.7874	35000	23200	0.449
SC211	55 2.1654	100 3.9370	21 0.8268	43500	29200	0.589
SC212	60 2.3622	110 4.3307	22 0.8661	47700	32900	0.774
SC302	15 0.5906	42 1.6535	13 0.5118	11440	5430	0.076
SC303	17 0.6693	47 1.8504	11914 0.5512	13585	6560	0.105
SC304	20 0.7874	52 2.0472	15 0.5906	15938	7810	0.137
SC305	25 0.9843	62 2.4409	17 0.6693	22400	11500	0.211
SC306	30 1.1181	72 2.8346	19 0.7480	26700	15000	0.338
SC307	35 1.3780	80 3.1496	5721 0.8268	33500	19100	0.439
SC308	40 1.5748	90 3.5433	23 0.9055	40500	24000	0.618
SC309	45 1.7717	100 3.9370	25 0.9843	52800	31800	0.810
SC310	50 1.9685	110 4.3307	27 1.0630	61800	39700	1.048
SC311	55 2.1654	120 4.7244	29 1.1417	71500	44700	1.326
SC312	60 2.3622	130 5.1181	31 1.2205	81700	51800	1.659